



CHAIN

SPECTRUM® 10 GRADE 100 ALLOY CHAIN

- Alloy Steel.
- Heat Treated.
- 25% stronger than Grade 80 Alloy Chain.
- Permanently embossed with CG (Crosby Group) and 10 (Grade).
- Finish - Black rust preventative coating.
- Proof Tested at 2 times the Working Load Limit with certification.
- Standard container - fiber drum.
- For further information and guidance refer to the latest Crosby catalogue available at www.thecrosbygroup.com

Crosby®



Chain size (mm)	(in.)	Stock code	Meters per drum	Dimensions (mm)	Working Load Limit (t)*	Weight per meter (kg)
7	9/32 (1/4)	XCRCHAIN07	200	7 x 21	2.0	1.05
8	5/16	XCRCHAIN08	200	8 x 24	2.5	1.25
10	3/8	XCRCHAIN10	200	10 x 30	4.0	2.20
13	1/2	XCRCHAIN13	150	13 x 39	6.7	3.80
16	5/8	XCRCHAIN16	100	16 x 48	10.0	5.70
19	3/4	XCRCHAIN19	50	19 x 57	14.0	8.03
22	7/8	XCRCHAIN22	50	23 x 69	21.0	10.9
23	7/8	XCRCHAIN23	50	23 x 69	21.0	10.9
26	1	XCRCHAIN26	50	26 x 78	26.5	15.2
32	1-1/4	XCRCHAIN32	20	32 x 96	40.0	23.0

* Proof tested at 2 times Working Load Limit. Ultimate Load is 4 times the Working Load Limit.