



HOOKS


GRADE 100 CLEVIS GRAB HOOKS

- Forged Alloy Steel - Quenched and Tempered.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby & U.S.A. in raised letters.
- Suitable for use with Grade 100 and Grade 80 chain.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color - Crosby Grade 100 Alloy Products."
- For further information and guidance refer to the latest Crosby catalogue available at www.thecrosbygroup.com


Crosby®



A-1358



L-1358



Chain size (mm)	(in.)	A-1338 stock code	L-1338 stock code	Weight each (kg)	Working Load Limit (t)*	Dimensions (mm)					S-4338 replacement latch kit stock code
						A	B	C	D	F	
7	1/4	XCRA1358-07	XCRL1358-07	0.20	2.0	43.7	64.5	55.9	98.5	22.4	XCRS4338-07
8	5/16	XCRA1358-08	XCRL1358-08	0.45	2.6	43.7	64.5	55.4	98.5	22.4	XCRS4338-08
10	3/8	XCRA1357-10	XCRL1357-10	0.82	4.0	47.0	78.5	65.5	119	27.7	XCRS4338-10
13	1/2	XCRA1357-13	XCRL1357-13	1.78	6.8	60.7	97.3	83.3	149	36.1	XCRS4338-13
16	5/8	XCRA1357-16	XCRL1357-16	3.18	10.3	67.8	115	97.8	179	44.5	XCRS4338-16

* Ultimate load is 4 times the Working Load Limit.