



HOOKS


GRADE 100 CLEVIS CRADLE GRAB HOOKS

- Forged Alloy Steel - Quenched and Tempered.
- Innovative cradle design allows for 100% efficiency of Grade 100 chain.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby & U.S.A. in raised letters.
- Suitable for use with Grade 100 and Grade 80 chain.
- The use of A-1338 Cradle Grab Hook will allow 100 percent of the chain sling capacity. When used to hook back to chain leg to form a choker, the angle of the choke must be 120 degrees or greater. When used as a chain shortener, minimize twist of chain and ensure chain is fully engaged in hook.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color - Crosby Grade 100 Alloy Products."
- For further information and guidance refer to the latest Crosby catalogue available at www.thecrosbygroup.com


Crosby



A-1338



L-1338



Chain size (mm)	(in.)	A-1338 stock code	L-1338 stock code	Weight each (kg)	Working Load Limit (t)*	Dimensions (mm)						S-4338 replacement latch kit stock code
						A	B	C	D	E	F	
7	1/4	XCRA1338-07	XCRL1338-07	0.20	2.0	43.7	64.5	55.9	98.5	38.1	22.4	XCRS4338-07
8	5/16	XCRA1338-08	XCRL1338-08	0.45	2.6	43.7	64.5	55.4	98.5	38.1	22.4	XCRS4338-08
10	3/8	XCRA1337-10	XCRL1337-10	0.82	4.0	47.0	78.5	65.5	119	46.5	27.7	XCRS4338-10
13	1/2	XCRA1337-13	XCRL1337-13	1.78	6.8	60.7	97.3	83.3	149	57.2	36.1	XCRS4338-13
16	5/8	XCRA1337-16	XCRL1337-16	3.18	10.3	67.8	115	97.8	179	74.5	44.5	XCRS4338-16

* Ultimate load is 4 times the Working Load Limit.