



HOOKS


GRADE 100 SHUR-LOC® EYE & CLEVIS HOOKS

- Forged Alloy Steel - Quenched and Tempered.
- 25% stronger than Grade 80.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Eye style is designed with "Engineered Flat" to connect to S-1325 chain coupler.
- Suitable for use with Grade 100 and Grade 80 chain.
- The SHUR-LOC® hook, if properly installed and locked, can be used for personnel lifting applications and meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color - Crosby Grade 100 Alloy Products."
- For further information and guidance refer to the latest Crosby catalogue available at www.thecrosbygroup.com


Crosby®



S-1316



S-1317



S-1316 Crosby SHUR-LOC® Eye Hook

Chain size (mm)	Chain size (in.)	S-1316 stock code	Weight each (kg)	Working Load Limit	Dimensions (mm)								
					A	C	D	E	F	H	J	L	AA
6	-	XCRS1316-06	0.39	1.5	19.8	100	20.1	66.0	17.0	7.87	16.0	29.5	38.1
7-8	1/4-5/16	XCRS1316-07	0.82	2.6	27.4	135	27.9	88.9	22.1	9.91	20.6	37.6	51.0
10	3/8	XCRS1316-10	1.54	4.0	33.0	167	29.7	112	27.9	12.9	23.9	46.5	63.5
13	1/2	XCRS1316-13	2.72	6.8	41.9	209	42.4	139	32.0	17.0	29.5	56.4	76.2
16	5/8	XCRS1316-16	6.85	10.3	55.9	256	51.8	167	38.1	22.1	38.1	67.3	89.0
18-20	3/4	XCRS1316-18	8.62	16.0	66.0	274	56.4	197	51.1	22.1	51.6	89.4	-
22	7/8	XCRS1316-22	12.7	20.0	72.9	317	62.2	222	57.7	24.9	55.9	97.3	-
26	1	XCRS1316-26	22.5	27.1	80.0	371	81.5	251	62.5	32.0	68.1	104	-

* Ultimate load is 4 times the Working Load Limit.

S-1317 Crosby SHUR-LOC® Clevis Hook

Chain size (mm)	Chain size (in.)	S-1317 stock code	Weight each (kg)	Working Load Limit (t)*	Dimensions (mm)								
					C	D	E	G	J	L		AA	
6	-	XCRS1317-06	0.35	1.5	87.4	20.1	66.0	121	16.0	29.0		38.1	
7	1/4	XCRS1317-07	0.82	2.0	114	27.9	89.0	159	20.6	35.1		51.0	
8	5/16	XCRS1317-08	0.82	2.6	114	27.9	89.0	159	20.6	35.1		51.0	
10	3/8	XCRS1317-10	1.66	4.0	140	29.7	112	192	24.1	46.5		63.5	
13	1/2	XCRS1317-13	3.08	6.8	173	42.4	139	242	29.5	56.4		76.2	
16	5/8	XCRS1317-16	5.40	10.3	209	51.8	167	295	38.1	67.3		89.0	
18-20	3/4	XCRS1317-18	6.80	16.0	239	56.4	197	336	51.6	89.4		-	
22	7/8	XCRS1317-22	12.7	20.0	283	62.2	222	392	55.9	97.3		-	
26	1	XCRS1317-26	22.5	27.1	319	81.5	251	468	68.1	104		-	

* Ultimate load is 4 times the Working Load Limit.