



HOOKS


GRADE 100 SHUR-LOC® SWIVEL HOOKS

- Forged Alloy Steel - Quenched and Tempered.
- Individually Proof Tested at 2-1/2 times the Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Rated for both Wire Rope, and use with Grade 80/100 Chain.
- G-414 Heavy Thimble should be used with wire rope slings.
- Trigger Repair Kit available (S-4316). Consists of spring, roll pin and trigger.
- S-13326 Swivel Hook utilizes anti-friction bearing design which allows hook to rotate freely under load.
- Fatigue rated.
- The SHUR-LOC® hook, if properly installed and locked, can be used for personnel lifting applications and meets the intent of OSHA Rule 1926.1431(g)(1)(i)(A) and 1926.1501(g)(4)(iv)(B).
- "Look for the Platinum Color – Crosby Grade 100 Alloy Products."
- U.S. Patent 5,381,650 and foreign equivalents. Use in corrosive environment requires shank and nut inspection in accordance with ASME B30.10-1.10.4(b)(5)(c)2009.
- For further information and guidance refer to the latest Crosby catalogue available at www.thecrosbygroup.com


Crosby®



S-1326



S-13326



S-1326 Crosby SHUR-LOC® Swivel Hook

Chain size		S-1326 stock code	Weight each (kg)	Grade 100 alloy chain Working Load Limit (t)*	Dimensions (mm)									
(mm)	(in.)				A	B	C	D	E	F	H	J	L	AA
6	—	XCRS1326-06	0.57	1.5	38.1	33.5	189	20.1	66.0	17.0	12.7	16.0	28.7	38.1
7-8	1/4-5/16	XCRS1326-07	1.18	2.6	44.5	40.4	235	27.9	88.9	22.1	16.0	20.6	35.1	51.0
10	3/8	XCRS1326-10	2.13	4.0	50.8	43.9	274	29.7	112	27.9	19.1	23.9	44.5	63.5
13	1/2	XCRS1326-13	3.92	6.8	63.5	60.5	351	42.4	139	32.0	25.4	29.5	53.6	76.2
16	5/8	XCRS1326-16	7.71	10.3	69.9	68.6	410	51.8	167	38.1	28.7	38.1	63.2	89.0
18-20	3/4	XCRS1326-18	10.9	16.0	71.9	64.0	442	56.4	197	51.1	27.9	51.6	89.4	127
22	7/8	XCRS1316-22	13.2	20.0	87.4	81.0	418	62.2	222	57.4	33.0	55.9	97.3	152

* Ultimate load is 4 times the Working Load Limit.

S-13326 Crosby SHUR-LOC® Swivel Hook

Chain size		S-13326 stock code	Weight each (kg)	Grade 100 alloy chain Working Load Limit (t)*	Dimensions (mm)									
(mm)	(in.)				A	B	C	D	E	F	H	J	L	AA
6	—	XCRS13326-06	0.57	1.5	38.1	29.0	157	20.1	66.0	17.0	12.7	16.0	28.7	38.1
7-8	1/4-5/16	XCRS13326-07	1.18	2.6	44.5	38.6	192	27.9	89.0	22.1	16.0	20.6	35.1	51.0
10	3/8	XCRS13326-10	2.13	4.0	51.0	40.9	226	29.7	112	27.9	19.1	23.9	46.5	63.5
13	1/2	XCRS13326-13	3.92	6.8	63.5	51.6	282	42.4	138	32.0	25.4	29.5	53.5	76.2
16	5/8	XCRS13326-16	7.71	10.3	70.0	57.2	320	52.0	167	38.1	28.7	38.1	63.0	89.0

* Ultimate load is 4 times the Working Load Limit.