



SWIVELS

BEARING BMM

- Against an extra charge all swivels can be tested and certified.



Steel - Tapered roller thrust bearing - Greaseable

Stock code	W.L.L. (ton)	Dimensions (mm)							Weight (kg)
		A	B	C	D	E	F	G	
SWIVELBLA401	1.0	126	43	16	15	36	18	35	0.78
SWIVELBLA402	2.0	157	54	20	20	45	22	45	1.55
SWIVELBLA403	3.0	189	65	27	26	55	28	55	2.7
SWIVELBLA405	5.0	220	70	33	30	64	33	60	3.95
SWIVELBLA408	8.0	250	85	42	34	73	39	75	6.8
SWIVELBLA412	12.0	295	95	50	41	86	45	86	10.75
SWIVELBLA417	17.0	360	120	57	45	113	55	108	20.4
SWIVELBLA422	22.0	435	131	60	52	118	63	118	24.7
SWIVELBLA432	32.0	500	160	65	59	132	73	140	45
SWIVELBLA445	45.0	700	220	102	74	190	100	200	130



Stainless steel - Tapered roller thrust bearing - Greaseable

Stock code	W.L.L. (ton)	Dimensions (mm)							Weight (kg)
		A	B	C	D	E	F		
SWIVELBLA402/1	2.0	157	54	20	20	45	22		1.5
SWIVELBLA403/1	3.0	189	65	27	26	55	28		2.75



Stainless steel - Bronze bushing

Stock code	W.L.L. (ton)	Dimensions (mm)							Weight (kg)
		A	B	C	D	E	F		
SWIVELBLA304/2	4.0	169	49	29	26	50	25		1.6
SWIVELBLA306/2	6.0	197	58	34	30	60	31		2.7
SWIVELBLA308/2	8.0	224	68	40	34	69	35		4.40



Steel - Tapered roller thrust bearing - Greaseable

Stock code	W.L.L. (ton)	Dimensions (mm)													Weight (kg)
		A	A ₁	B	B ₁	B ₂	B ₃	C ₁	C ₂	D	E	F	G		
SWIVELBLA810T/3*	10.0	195	160	115	13	11	18	19	43	14	37	20	33		8.7
SWIVELBLA810G/3*	10.0	195	160	115	13	11	18	19	43	15	37	20	33		8.7
SWIVELBLA812/3	12.0	200	162	135	17	14	22	23	49	17	40	20	38		9.7
SWIVELBLA817/3	17.0	250	208	150	21	16	25	27	57	20	53	29	47		17.3

* T = Crosby Trawllex, G = Gunnebo.

Connector not included.

Replacement bearings and seals can be ordered,
contact African Maritime Services (PTY) Ltd. for further information.

