




TRAWL WARPS

MARBLUE


Large outer wires for increased wear and abrasion resistance.

- Large outer wires for increased abrasion resistance
- Poly core provides increased flexibility
- IWRC for high strength

BRIDON · BEKAERT
THE ROPES GROUP



6x19
(9/9/1) Poly Core



6x19
(9/9/1) IWRC

Poly Core				IWRC Steel Core			
Diameter mm	Weight kg/100m	Minimum Breaking Load		Weight kg/100m	Minimum Breaking Load		
		Tonnes	kN		Tonnes	kN	
12	52.3	8.4	82	58.9	9.03	89	
14	70.4	11.4	112	80.7	12.1	119	
16	90.9	14.9	146	102	16.2	159	
18	116.8	18.8	184	128.9	20.5	201	
20	144.2	23.3	228	164.6	25.1	246	
22	175.1	28.2	277	199.7	30.4	298	
24	205.4	33.6	330	235.4	36.1	354	
26	241.4	39.3	385	276.9	42.4	416	
27	261.8	42.5	417	294.9	47.3	464	
28	279.2	45.7	448	318.9	49.3	483	
30	315.6	48.4	475	383.2	56.5	554	
32	370	59.5	583	411	64.2	630	
34	422.8	67.2	659	460.1	72.5	711	