


TRAWL WARPS

DYFORM® Starfish


High strength and proven extended rope life - preventing core corrosion and maintaining design diameter.

- Superior bend fatigue
- Crush resistant
- Long service life
- Reduced elongation

BRIDON · BEKAERT
THE ROPES GROUP



6x26
(10/5&5/5/1) Poly Core



6x26
(10/5&5/5/1) IWRC

Diameter mm	Poly Core			IWRC Steel Core		
	Weight kg/100m	Minimum Breaking Load		Weight kg/100m	Minimum Breaking Load	
		Tonnes	kN		Tonnes	kN
16	103.3	17.4	171	115.5	19.6	192
18	129.1	22.4	220	145.3	25.2	247
20	159.7	26.4	259	183	30.5	299
22	191.7	32.9	323	216.6	37	363
24	224.8	38.3	376	254.7	43.5	427
26	271.5	46.3	454	307.2	52	510
28	317.4	52	510	351.7	58.4	573
30	357.3	58.1	570	403.8	67.2	659
32	408.8	68.3	670	461.1	78.2	767
34	468.2	77.5	760	527.2	88.7	870
36	514.5	87.4	857	599.4	100	981
38	578.6	92.7	909	661.1	103	1010
40	635.2	102.7	1007	725.4	117.5	1152
42	700.3	119.7	1174	799.3	137	1344